KIGBM

JOGI

Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+10°C. Worktop 60 mm thick in AISI 304 stainless steel. Depth 70 cm. GN 1/1.3 doors. Control panel with digital thermometer - thermostat and communication port. Automatic defrosting electric type.



 ϵ

General information

Supplier/producer 's name	SAGI
Series	l-green
Supplier's model identifier	KIGBM
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	-2/+10
Energy Efficiency Class	A
Energy consumption, kWh/24h	1,52
Energy consumption/year, kWh/a	556
Method for energy consumption	EN 22041
Energy Efficiency Index	23,1
Net usable volume, it	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic by heating elements

Refrigerated counter-GN1/1-AISI 304-I-green





Refrigerated counter-GN1/1-AISI 304-I-green

KIGBM

Evaporation of condense drain



automatic
406
230V 1N~ / 50Hz
0,22
one-piece structure with rounded internal corners
AISI 304 stainless steel
AISI 304 stainless steel
with rounded corners
60
worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
AISI 304 stainless steel grid-supporting rack
11/40,5
with an anti-corrosion treatment
the cooling unit pulls out to simplify routine cleaning of the condense
stainless steel AISI 304, adjustable in height
140 ÷ 200
3 doors
digital thermometer/thermostat and communication port
digital
32,5x53 GN1/1
complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio
192x76x90
185x70x90
149
137
Drawer accessories (conveyor panel on the inner ceiling of the appliance must be removed).

automatic