

KIGC2A



Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat and communication port. Automatic defrosting electric type.



General information

| | |
|-----------------------------|----------------------|
| Series | I-green |
| Supplier's model identifier | KIGC2A |
| Category | counter cabinet |
| Type | refrigerated counter |
| Line | catering - GN 1/1 |

Technical features

| | |
|--------------------------------|--|
| Temperature ranges, °C | -2/+10 |
| Energy Efficiency Class | B |
| Energy consumption, kWh/24h | 2,42 |
| Energy consumption/year, kWh/a | 885 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 34,7 |
| Net usable volume, lt | 298 |
| Volume, gross, lt | 578 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,08 |
| LWA dB(A) | 50 |
| Cooling system | ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability |
| Defrosting | automatic by heating elements |
| Evaporation of condense drain | automatic |

Refrigerated counter-GN1/1-AISI 304-I-green



| | |
|--------------------------------|-----------------|
| Refrigeration power at -10°C W | 560 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,28 |

Construction features

| | |
|---------------------------|---|
| Structure | one-piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | with rounded corners |
| Insulation thickness, mm | 60 |
| Worktop | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 11/40,5 |
| Evaporator | with an anti-corrosion treatment |
| Easymaintenance | the cooling unit pulls out to simplify routine cleaning of the condenser |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Equipped with | door and drawers |
| Drawers, type: 1/2 | 2 |

Control and functions

| | |
|-----------------|---|
| Kinf of control | digital thermometer/thermostat and communication port |
| Display | digital |

Standard

| | |
|------------------------------|--|
| Shelf's dimensions, cm | 32,5x53 GN1/1 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |

Dimensions and weights

| | |
|------------------------|----------------|
| Packing (LxDxH), cm | 235,5x75,5x100 |
| Dimensions (LxDxH), cm | 230x70x98,5 |
| Gross Weight (kg) | 187 |
| Net Weight (kg) | 172 |

Refrigerated counter-GN1/1-AISI 304-I-green