

Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body.Temperature ranges:
0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel.Depth 70
cm.GN 1/1.3 doors.Control panel with digital thermometer -
thermostat.



General information

Supplier/producer 's name	SAGI
Series	Universal
Supplier's model identifier	KUBM
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption, kWh/24h	2,704
Energy consumption/year, kWh/a	987
Method for energy consumption	EN 22041
Energy Efficiency Index	41,02
Net usable volume, lt	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-AISI 304-Universal

Evaporation of condense drain	automatic
Refrigeration power at -10°C W	465
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,28

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Equipped with	3 doors

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packing (LxDxH), cm	192x76x90
Dimensions (LxDxH), cm	185x70x90
Gross Weight (kg)	147
Net Weight (kg)	135