XE70B

JOGI

Freezer-press-formed sides GN2/1-X-treme

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press–formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 1 door. Temperature ranges: -22/-15°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. High efficiency motor unit. Automatic defrosting by hot gas. Lighting and key-operated lock.



 ϵ

General information

Supplier/producer 's name	SAGI
Series	X-TREME
Supplier's model identifier	XE70B
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1

Technical features

cimical reacares	
Temperature ranges, °C	-22/-15
Energy Efficiency Class	С
Energy consumption, kWh/24h	4,38
Energy consumption/year, kWh/a	1599
Method for energy consumption	EN 22041
Energy Efficiency Index	43,04
Net usable volume, It	455
Volume, gross, lt	521
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,110
LWA dB(A)	39
Cooling system	ventilated refrigeration system
Defrosting	automatic by hot gas
Evaporation of condense drain	automatic

Freezer-press-formed sides GN2/1-X-treme





XE70B



Refrigeration pow	ver -23,3°C W	611
Frequency/voltag	e	230V 1N~ / 50Hz
Electric power, kV	V	0,67
Construction feat	tures	
Structure		one - piece structure with rounded internal corners
External material		AISI 304 stainless steel
Internal material		AISI 304 stainless steel
Internal bottom		diamond treated bottom
Insulation thickne	ess, mm	75
Door		1 door in AISI 304 stainless steel
Standard hinging	door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle		integrated full-height
Internal structure		with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spa	ced, mm	20/55
Evaporator		positioned outside the compartment
Easymaintenance		accessibility to all the functional and control components via a retractable front panel
Safety interlock s	witch	yes, to stop internal fan and switch on compartment light
Feet		stainless steel AISI 304, adjustable in height
Height of feet, mr	m	115 ÷ 165
Control and func	tions	
Kinf of control		electronic pannel control board
Display		digital
Connectivity		with APOLINK accessory for remote control – Industry 4.0
Alarms		optical and acoustical
Functions/progra	ms	Hyper Cold, Energy Saving and setting of the relative humidity to 75% or to 90%
Standard		
Key-lock		yes
Lighting		yes
Shelves (n.)		4 AISI 304 stainless steel 53x65cm (GN 2/1) + 1 AISI 304 stainless steel 50x62cm
Shelf loading capa	acity, kg	60
Dimensions and v	weights	
Packing (LxDxH),	cm	79x85,5x218
Dimensions (LxD)	kH), cm	68,4x80x204
Gross Weight (kg)		140
Net Weight (kg)		125